


PROFILE PROSTOKĄTNE KONSTRUKCYJNE

wg PN-EN 10219

długości: 6000-12000 -0/+100 mm i inne po uzgodnieniu

gatunki: S235JRH, S355J2H i inne po uzgodnieniu



Kolorem niebieskim oznaczono zakres produkcji.

Oferta magazynowa obejmuje część wymiarów.

Wymiary [mm]		Grubość ścianki S [mm]									
A	B	1,5	2,0	2,5	3,0	4,0	5,0	6,0	8,0	10,0	12,5
20	10	■									
	15	■	■								
25	10	■									
	15	■	■								
	20	■	■								
30	10	■									
	15	■	■	■							
	18	■	■	■							
	20	■	■	■	■						
35	25	■	■								
	15	■	■								
	20	■	■	■							
	25	■	■	■	■						
40	30	■	■	■	■						
	10	■									
	15	■	■								
	20	■	■	■	■						
	25	■	■	■	■	■					
	27	■	■	■	■	■					
	30	■	■	■	■	■					
45	35	■	■	■	■	■					
	20	■									
	25	■	■	■	■						
50	30	■	■	■	■	■					
	10	■									
	15	■	■	■							
	20	■	■	■	■						
	25	■	■	■	■	■					
	30	■	■	■	■	■	■				
50	40	■	■	■	■	■	■				
	40	■	■	■	■	■	■				

PROFILE PROSTOKĄTNE KONSTRUKCYJNE (ciąg dalszy)

wg PN-EN 10219

Kolorem niebieskim oznaczono zakres produkcji.

Oferta magazynowa obejmuje część wymiarów.

Wymiary [mm]		Grubość ścianki S [mm]									
A	B	1,5	2,0	2,5	3,0	4,0	5,0	6,0	8,0	10,0	12,5
55	20										
	25										
	35										
	40										
60	10										
	15										
	20										
	30										
	35										
	40										
	50										
70	20										
	30										
	40										
	50										
	60										
80	20										
	30										
	40										
	50										
	60										
90	30										
	40										
	50										
	60										
100	20										
	30										
	40										
	50										
	60										
	80										

PROFILE PROSTOKĄTNE KONSTRUKCYJNE (ciąg dalszy)

wg PN-EN 10219

Kolorem niebieskim oznaczono zakres produkcji.

Oferta magazynowa obejmuje część wymiarów.

Wymiary [mm]		Grubość ścianki S [mm]									
A	B	1,5	2,0	2,5	3,0	4,0	5,0	6,0	8,0	10,0	12,5
120	30										
	40										
	50										
	60										
	80										
	100										
140	40										
	50										
	60										
	70										
	80										
	100										
150	50										
	75										
	100										
160	60										
	80										
	90										
	100										
	120										
180	60										
	80										
	100										
	120										
200	80										
	100										
	120										
	150										
250	100										
	150										
300	100										
	200										