

RURY DO PRZESYŁU MEDIÓW PALNYCH


wg PN-EN 10208-2 i PN-EN ISO 3183

długości: 6000-12000 -0/+300 mm i inne po uzgodnieniu

gatunki: L360NB, L360NE i inne po uzgodnieniu

Kolorem niebieskim oznaczono zakres produkcji.

Oferta magazynowa obejmuje część wymiarów.



| Średnica zewnętrzna | Grubość ścianki S [mm] | | | | | | | | | | | | | | | |
|---------------------|------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|--|
| | 2,6 | 2,9 | 3,2 | 3,6 | 4,0 | 4,5 | 5,0 | 5,6 | 6,3 | 7,1 | 8,0 | 8,8 | 10,0 | 11,0 | 12,5 | |
| Ø 21,3 | | | | | | | | | | | | | | | | |
| Ø 26,9 | | | | | | | | | | | | | | | | |
| Ø 33,7 | | | | | | | | | | | | | | | | |
| Ø 42,4 | | | | | | | | | | | | | | | | |
| Ø 48,3 | | | | | | | | | | | | | | | | |
| Ø 60,3 | | | | | | | | | | | | | | | | |
| Ø 76,1 | | | | | | | | | | | | | | | | |
| Ø 88,9 | | | | | | | | | | | | | | | | |
| Ø 101,6 | | | | | | | | | | | | | | | | |
| Ø 108,0 | | | | | | | | | | | | | | | | |
| Ø 114,3 | | | | | | | | | | | | | | | | |
| Ø 139,7 | | | | | | | | | | | | | | | | |
| Ø 159,0 | | | | | | | | | | | | | | | | |
| Ø 168,3 | | | | | | | | | | | | | | | | |
| Ø 219,1 | | | | | | | | | | | | | | | | |
| Ø 273,0 | | | | | | | | | | | | | | | | |

W przypadku zainteresowania innymi pozycjami prosimy o przesłanie zapytania ofertowego.

