

RURY KONSTRUKCYJNE BEZ SZWU WALCOWANE NA GORĄCO


wg PN-EN 10210 i PN-EN 10297-1

długości: 6000-12000 -0/+300 mm i inne po uzgodnieniu

gatunki: S235JRH, S355J2H, E355 i inne po uzgodnieniu

Kolorem niebieskim oznaczono zakres produkcji.

Oferta magazynowa obejmuje część wymiarów.



| Średnica zewnętrzna | Grubość ścianki S [mm] | | | | | | | | | | | | | | | | | | | | |
|---------------------|------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|
| | 2,0 | 2,3 | 2,6 | 2,9 | 3,2 | 3,6 | 4,0 | 4,5 | 5,0 | 5,6 | 6,3 | 7,1 | 8,0 | 8,8 | 10,0 | 11,0 | 12,5 | 14,2 | 16,0 | 17,5 | 20,0 |
| Ø 21,3 | | | | | | | | | | | | | | | | | | | | | |
| Ø 25,0 | | | | | | | | | | | | | | | | | | | | | |
| Ø 26,9 | | | | | | | | | | | | | | | | | | | | | |
| Ø 30,0 | | | | | | | | | | | | | | | | | | | | | |
| Ø 31,8 | | | | | | | | | | | | | | | | | | | | | |
| Ø 33,7 | | | | | | | | | | | | | | | | | | | | | |
| Ø 38,0 | | | | | | | | | | | | | | | | | | | | | |
| Ø 42,4 | | | | | | | | | | | | | | | | | | | | | |
| Ø 44,5 | | | | | | | | | | | | | | | | | | | | | |
| Ø 48,3 | | | | | | | | | | | | | | | | | | | | | |
| Ø 51,0 | | | | | | | | | | | | | | | | | | | | | |
| Ø 54,0 | | | | | | | | | | | | | | | | | | | | | |
| Ø 57,0 | | | | | | | | | | | | | | | | | | | | | |
| Ø 60,3 | | | | | | | | | | | | | | | | | | | | | |
| Ø 63,5 | | | | | | | | | | | | | | | | | | | | | |
| Ø 70,0 | | | | | | | | | | | | | | | | | | | | | |

RURY KONSTRUKCYJNE BEZ SZWU WALCOWANE NA GORĄCO (ciąg dalszy)


wg PN-EN 10210 i PN-EN 10297-1

długości: 6000-12000 -0/+300 mm i inne po uzgodnieniu

gatunki: S235JRH, S355J2H, E355 i inne po uzgodnieniu

Kolorem niebieskim oznaczono zakres produkcji.

Oferta magazynowa obejmuje część wymiarów.



| Średnica zewnętrzna | Grubość ścianki S [mm] | | | | | | | | | | | | | | | | | | | | | | | |
|---------------------|------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|------|------|------|------|------|------|------|--|
| | 2,9 | 3,2 | 3,6 | 4,0 | 4,5 | 5,0 | 5,6 | 6,3 | 7,1 | 8,0 | 8,8 | 10,0 | 11,0 | 12,5 | 14,2 | 16,0 | 17,5 | 20,0 | 22,2 | 25,0 | 28,0 | 30,0 | 40,0 | |
| Ø 73,0 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 76,1 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 82,5 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 88,9 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 95,0 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 101,6 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 108,0 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 114,3 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 121,0 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 127,0 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 133,0 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 139,7 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 146,0 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 152,4 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 159,0 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 168,3 | | | | | | | | | | | | | | | | | | | | | | | | |
| Ø 177,8 | | | | | | | | | | | | | | | | | | | | | | | | |

RURY KONSTRUKCYJNE BEZ SZWU WALCOWANE NA GORĄCO (ciąg dalszy)


wg PN-EN 10210 i PN-EN 10297-1

długości: 6000-12000 -0/+300 mm i inne po uzgodnieniu

gatunki: S235JRH, S355J2H, E355 i inne po uzgodnieniu

Kolorem niebieskim oznaczono zakres produkcji.

Oferta magazynowa obejmuje część wymiarów.



| Średnica zewnętrzna | Grubość ścianki S [mm] | | | | | | | | | | | | | | | | | | | | | |
|---------------------|------------------------|-----|-----|-----|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|--|
| | 5,6 | 6,3 | 7,1 | 8,0 | 8,8 | 10,0 | 11,0 | 12,5 | 14,2 | 16,0 | 17,5 | 20,0 | 22,2 | 25,0 | 28,0 | 30,0 | 32,0 | 36,0 | 40,0 | 45,0 | 50,0 | |
| Ø 193,7 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 203,0 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 219,1 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 229,0 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 244,5 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 254,0 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 267,0 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 273,0 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 298,5 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 323,9 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 355,6 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 368,0 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 406,4 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 457,0 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 508,0 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 559,0 | | | | | | | | | | | | | | | | | | | | | | |
| Ø 610,0 | | | | | | | | | | | | | | | | | | | | | | |