

RURY KONSTRUKCYJNE ZE SZWEM


wg PN-EN 10219 i PN-EN 10210

długości: 6000-12000 -0/+50 mm i inne po uzgodnieniu

gatunki: S235JRH, S355J2H i inne po uzgodnieniu

Kolorem niebieskim oznaczono zakres produkcji.

Oferta magazynowa obejmuje część wymiarów.



Średnica zewnętrzna	Grubość ścianki S [mm]														
	1,5	2,0	2,3	2,6	2,9	3,2	3,6	4,0	4,5	5,0	5,6	6,3	8,0	10	12,5
Ø 17,2															
Ø 21,3															
Ø 26,9															
Ø 33,7															
Ø 42,4															
Ø 44,5															
Ø 48,3															
Ø 50,8															
Ø 51,0															
Ø 54,0															
Ø 57,0															
Ø 60,3															
Ø 63,5															
Ø 70,0															
Ø 76,1															
Ø 80,0				2,5	3,0										
Ø 88,9															
Ø 101,6															
Ø 108,0															
Ø 114,3															
Ø 127,0															
Ø 133,0															
Ø 139,7															
Ø 152,4															
Ø 159,0															
Ø 168,3															
Ø 177,8															
Ø 193,7															
Ø 219,1															
Ø 244,5															
Ø 273,0															
Ø 323,9															

W przypadku zainteresowania innymi pozycjami, prosimy o przesłanie zapytania ofertowego.