

RURY PRZEWODOWE BEZ SZWU WALCOWANE NA GORĄCO


wg PN-EN 10216-1 i PN-EN 10216-3

długości: 6000-12000 -0/+300 mm i inne po uzgodnieniu

gatunki: P235TR2, P355NH-TC1, P355NL1-TC1 i inne po uzgodnieniu

Kolorem niebieskim oznaczono zakres produkcji.

Oferta magazynowa obejmuje część wymiarów.



Średnica zewnętrzna	Grubość ścianki S [mm]																				
	2,0	2,3	2,6	2,9	3,2	3,6	4,0	4,5	5,0	5,6	6,3	7,1	8,0	8,8	10,0	11,0	12,5	14,2	16,0	17,5	
Ø 21,3																					
Ø 25,0																					
Ø 26,9																					
Ø 30,0																					
Ø 31,8																					
Ø 33,7																					
Ø 38,0																					
Ø 42,4																					
Ø 44,5																					
Ø 48,3																					
Ø 51,0																					
Ø 54,0																					
Ø 57,0																					
Ø 60,3																					
Ø 63,5																					
Ø 70,0																					

RURY PRZEWODOWE BEZ SZWU WALCOWANE NA GORĄCO (ciąg dalszy)


wg PN-EN 10216-1 i PN-EN 10216-3

długości: 6000-12000 -0/+300 mm i inne po uzgodnieniu

gatunki: P235TR2, P355NH-TC1, P355NL1-TC1 i inne po uzgodnieniu

Kolorem niebieskim oznaczono zakres produkcji.

Oferta magazynowa obejmuje część wymiarów.



Średnica zewnętrzna	Grubość ścianki S [mm]																						
	2,9	3,2	3,6	4,0	4,5	5,0	5,6	6,3	7,1	8,0	8,8	10,0	11,0	12,5	14,2	16,0	17,5	20,0	22,2	25,0	28,0	30,0	32,0
Ø 73,0																							
Ø 76,1																							
Ø 82,5																							
Ø 88,9																							
Ø 95,0																							
Ø 101,6																							
Ø 108,0																							
Ø 114,3																							
Ø 121,0																							
Ø 127,0																							
Ø 133,0																							
Ø 139,7																							
Ø 146,0																							
Ø 152,4																							
Ø 159,0																							
Ø 168,3																							
Ø 177,8																							

RURY PRZEWODOWE BEZ SZWU WALCOWANE NA GORĄCO (ciąg dalszy)


wg PN-EN 10216-1 i PN-EN 10216-3

długości: 6000-12000 -0/+300 mm i inne po uzgodnieniu

gatunki: P235TR2, P355NH-TC1, P355NL1-TC1 i inne po uzgodnieniu

Kolorem niebieskim oznaczono zakres produkcji.

Oferta magazynowa obejmuje część wymiarów.



Średnica zewnętrzna	Grubość ścianki S [mm]																		
	5,6	6,3	7,1	8,0	8,8	10,0	11,0	12,5	14,2	16,0	17,5	20,0	22,2	25,0	28,0	30,0	32,0	36,0	40,0
Ø 193,7																			
Ø 203,0																			
Ø 219,1																			
Ø 229,0																			
Ø 244,5																			
Ø 254,0																			
Ø 267,0																			
Ø 273,0																			
Ø 298,5																			
Ø 323,9																			
Ø 355,6																			
Ø 406,4																			
Ø 457,0																			
Ø 508,0																			
Ø 559,0																			
Ø 610,0																			