


RURY PRZEWODOWE ZE SZWEM

wg PN-EN 10217-1, PN-EN 10255 i PN-EN 10224

długości: 6000-12000 -0/+50 mm i inne po uzgodnieniu

gatunki: P235TR1, L235, S195T, P235GH i inne po uzgodnieniu



Kolorem niebieskim oznaczono zakres produkcji.

Oferta magazynowa obejmuje część wymiarów.

Średnica zewnętrzna	Grubość ścianki S [mm]														
	2,0	2,3	2,6	2,9	3,2	3,6	4,0	4,5	5,0	5,6	6,3	7,1	8,0	10	12,5
Ø 17,2															
Ø 21,3															
Ø 26,9															
Ø 33,7															
Ø 38,0															
Ø 42,4															
Ø 48,3															
Ø 51,0															
Ø 57,0															
Ø 60,3															
Ø 63,5															
Ø 70,0															
Ø 76,1															
Ø 82,5															
Ø 88,9															
Ø 101,6															
Ø 108,0															
Ø 114,3															
Ø 127,0															
Ø 133,0															
Ø 139,7															
Ø 152,4															
Ø 159,0															
Ø 168,3															
Ø 177,8															
Ø 193,7															
Ø 219,1															
Ø 244,5															
Ø 273,0															
Ø 323,9															
Ø 355,6															
Ø 406,4															
Ø 457,0															
Ø 508,0															
Ø 610,0															
Ø 711,0															