

RURY PRZEWODOWE ZE SZWEM


wg PN-EN 10217-1, PN-EN 10255 i PN-EN 10224

długości: 6000-12000 -0/+50 mm i inne po uzgodnieniu

gatunki: P235TR1, L235, S195T, P235GH i inne po uzgodnieniu

Kolorem czerwonym oznaczono zakres produkcji.

Oferta magazynowa obejmuje część wymiarów.



Średnica zewnętrzna	Grubość ścianki S [mm]															
	2,0	2,3	2,6	2,9	3,2	3,6	4,0	4,5	5,0	5,6	6,3	7,1	8,0	10	12,5	
Ø 17,2																
Ø 21,3																
Ø 26,9																
Ø 33,7																
Ø 38,0																
Ø 42,4																
Ø 48,3																
Ø 51,0																
Ø 57,0																
Ø 60,3																
Ø 63,5																
Ø 70,0																
Ø 76,1																
Ø 82,5																
Ø 88,9																
Ø 101,6																
Ø 108,0																
Ø 114,3																
Ø 127,0																
Ø 133,0																
Ø 139,7																
Ø 152,4																
Ø 159,0																
Ø 168,3																
Ø 177,8																
Ø 193,7																
Ø 219,1																
Ø 244,5																
Ø 273,0																
Ø 323,9																
Ø 355,6																
Ø 406,4																
Ø 457,0																
Ø 508,0																
Ø 610,0																
Ø 711,0																